



ExecDoor[®] 2

CERTIFIED TO LPS 1175 ISSUE 7 LEVEL SR2

Single, leaf-and-a-half and double leaf, outward opening doorsets with single-point locking and vision panel option.



SECURITY



INDUSTRIAL




Applications

- Leisure facilities
- Schools and universities
- Housing association communal areas
- General retail outlets



ExecDoor® 2

Features

- Comprehensive range of locking options across both single and double leaf doorsets.
- Police Preferred Specification. 
- All doors hung on stainless steel hinges.
- Heavy duty barrel bolts fitted as standard to all double doorsets.
- Strong 1.5mm Electro-Zinc coated steel for maximum corrosion resistance.
- 45mm composite door leaves with incorporated anti-lever lip to closing edge.
- Single rebate threshold (welded to frame) providing rigid and strengthened frame set.
- Available in a wide range of powder coatings to BS or RAL colours.
- Can be fitted with our ExcluGlass® vision panel.

Frame Construction

Frame: Welded construction

Material: 1.5mm Zintec steel

Profile: Single rebated 38mm x 100mm

Reinforcing: At all hinges, lock keeps and fixing points

Door Leaf Construction

Material: 1.5mm Zintec attack face with 1.5mm inner face. Double leafs are internally protected with sheets and reinforced with anti-crush plates and strengthening brackets.

Size: 45mm thick composite door leaf with incorporated astragal lip to closing edge.

Weight: Approximately 40-65 kg per square metre (depending on model).

Locking Options

High security locking from ASSA and panic furniture from Exidor a wide range of locks and options are available.

Heavy duty barrel bolts are fitted as standard to the passive leaf of double doorsets.

Locking types

- Panic escape
- Key driven

Hinges

Single: hung on 4" x 3" stainless steel hinges with a minimum of 4 per leaf.

Double: hung on 4" x 3" stainless steel hinges with a minimum of 4 per leaf with top and bottom heavy-duty barrel bolts as standard on passive leaf.

Vision Panel

Can be fitted with our ExcluGlass® 2 Vision Panel when both security and vision are important.

Finish

One coat of grey etch primer as standard for on-site finishing, or there is the option of a wide selection of powder coated colours from our own factory powder coating facility.

Single rebate threshold



Material: 1.5mm Zintec steel

Profile: Low level with stop threshold (welded to frame) - most common and suitable threshold for a range of applications.

Structural Opening Sizes (mm)

	Min width	Max width	Min height	Max height
Single leaf	750	1300	1800	2200
Double leaf	1500	2500	1800	2200



*Heavy duty
barrel bolt.*



Panic escape push bar option.



*Key driven option with
thumbturn.*




*ExcluGlass® 2 rated vision
panel.*



*Optional Vistamatic Sherman
vision panel.*

Bespoke design services



Complementing our standard door ranges we also offer a complete, bespoke design service to suit specific client needs or to overcome site/building constraints.

Sunray installation service



We offer an installation service covering our steel door, louvre systems and ExcluDoor® security door ranges.

Work is carried out by our own qualified factory-skilled operatives, not sub-contractors.

Procedures are audited and our installation process is approved and certified by CHAS, Safe Contractor, Achilles Builders Confidence and Achilles UVDB.

Sunray's Installation Service is certified by the LPCB/BRE to LPS 1271 for security doors.



Newly installed ExecDoor® 2 double doorset specified with vision panels

Nationwide delivery service

Specialist transport including arctics, curtain sidlers with Moffett facility, flat bed lorries with HIAB facility and lightweight vans including Crossrail compliant vehicles.



Sunray Engineering Ltd
Kingsnorth Industrial Estate
Wotton Road, Ashford, Kent TN23 6LL

T 01233 639039

E sales@sunraydoors.co.uk
www.sunraydoors.co.uk



**FIND OUT MORE
FROM THE SUNRAY
WEBSITE**

